

**CRUISE PERFORMANCE**  
**PRESSURE ALTITUDE 10,000 FEET**

CONDITIONS:  
4630 Pounds  
Recommended Lean Mixture  
Cowl Flaps Closed

**NOTE**

For best fuel economy at 65% power or less, operate each engine at 6 PPH leaner fuel flow or at peak EGT if an EGT indicator is installed.

		20°C BELOW STANDARD TEMP -25°C			STANDARD TEMPERATURE -5°C			20°C ABOVE STANDARD TEMP 15°C		
RPM	MP	% BHP	KTAS	TOTAL PPH	% BHP	KTAS	TOTAL PPH	% BHP	KTAS	TOTAL PPH
2600	19	65	160	119	63	160	115	61	160	111
	18	60	154	110	58	153	106	56	153	103
	17	55	146	101	53	146	98	51	146	95
	16	50	139	92	48	138	89	46	136	86
2500	19	62	156	114	60	156	110	58	156	106
	18	57	150	105	55	149	102	53	149	98
	17	52	143	97	50	142	93	49	141	91
	16	47	135	88	45	133	85	44	131	83
2400	19	58	151	107	56	151	103	54	151	100
	18	54	145	99	52	144	96	50	144	93
	17	49	138	91	47	137	88	46	135	86
	16	44	130	84	43	128	81	41	125	79
2300	19	54	146	100	52	145	97	51	145	94
	18	50	139	93	48	138	90	46	137	87
	17	46	132	85	44	130	83	42	127	80
2200	19	51	141	94	49	140	91	47	139	88
	18	47	134	87	45	132	84	43	130	82

Figure 5-13. Cruise Performance (Sheet 5 of 6)